

Website Monitoring - Bug #2373

HTTP/403 when proxy settings are defined in environment variables

03/25/2019 04:01 PM - Luke Murphey

Status:	Closed	Start date:	03/25/2019
Priority:	Normal	Due date:	
Assignee:	Luke Murphey	% Done:	100%
Category:		Estimated time:	0.00 hour
Target version:	2.7.4		
Description https://answers.splunk.com/answers/713179/website-monitoring-web-ping-logs-returns-a-respons.html#answer-736447 To reproduce the issue, add proxy settings to /opt/splunk/etc/splunk-launch.conf: <pre>HTTP_PROXY = XXXXX HTTPS_PROXY = XXXXX</pre>			

Associated revisions

Revision 446 - 03/25/2019 08:02 PM - lukemurphey

Adding ability to define a proxy override list

Closes #2373

History

#1 - 03/25/2019 05:09 PM - Luke Murphey

Observations:

- I found that the proxy is used when I set the environment variables

Questions:

- How is the customer saying that the proxy is not being used?
- Is the customer's proxy using authentication?
- Do the customers want to disable the proxy?
- How can I disable the proxy in requests?
 - <https://stackoverflow.com/questions/28521535/requests-how-to-disable-bypass-proxy/28521696>
 - This works: `os.environ['no_proxy'] = '**'`
 - This doesn't work: `session.trust_env = False`

#2 - 03/25/2019 10:53 PM - Luke Murphey

- Status changed from New to Closed

- % Done changed from 0 to 100